



DOOR SCHEDULE	R.O.	WINDOW SCHEDULE (FOR GLAZING SEE I1)	R.O.	COLUMN SUPPORT
1 36"x80" EXTERIOR	38"x82 3/8"	A 30"x60"	30 1/4"x60 1/4"	(A) 2-2x3'S (E) 6-2x3'S
2 32"x80" EXTERIOR	34"x82 3/8"	B 36"x60" EGRESS	36 1/4"x60 1/4"	(B) 3-2x3'S
3 30"x80" INTERIOR	32"x82 3/8"	C 30"x36	30 1/4"x36 1/4"	(C) 4-2x3'S
4 24"x80" INTERIOR	26"x82 3/8"	D 24"x48"	24 1/4"x48 1/4"	(D) 5-2x3'S
5 72"x80" SG GLASS DOOR	72"x80"	E 42"x34" BLOCK SAFETY GLAZED	42 1/4"x34 1/4"	AREA
6 48"x80" BIFOLD	50"x82 3/8"	F 30"x15" ROUND	30 1/4"x15 1/4"	1st FLOOR
7 60"x80" BIFOLD	62"x82 3/8"	G 30"x60" SAFETY GLAZED	30 1/4"x60 1/4"	1551 SQ. FT.
8 72"x80" ATRIUM DOOR	75 1/2"x82 1/4"	H 46"x60" SAFETY GLAZED	46 1/4"x60 1/4"	NOTE ALL WINDOWS:
9 32"x80" EXTERIOR	34"x82 3/8"	I 14"x68" SAFETY GLAZED	14 1/4"x68 1/4"	SHGC: 0.27 U:0.32
10 20"x80" INTERIOR	22"x82 3/8"	J 36"x60" EGRESS	36 1/4"x60 1/4"	NOTES:
11 36"x80" INTERIOR	38"x82 3/8"	K 36"x62" EGRESS	36 1/4"x62 1/4"	1. SEE ENERGY CALCULATIONS FOR NOTE:
12 32"x80" SOLID INTERIOR	34 1/2"x82 3/8"	L 30"x54" DORMER	30 1/4"x54 1/4"	ALLOWABLE WINDOW/DOOR OPTION ALL 1st AND 2nd FLOOR WINDOWS SHALL BE INSTALLED WITH THE LOWEST
13 72"x80" FRENCH DOOR	74 1/2"x82 1/4"	M 36"x68" EGRESS	36 1/4"x68 1/4"	COMBINATIONS. PART OF THE CLEAR OPENING LOCATED GREATER THAN 24" ABOVE THE FLOOR. IF THIS
		N 36"x66" EGRESS	36 1/4"x66 1/4"	REQUIREMENT IS NOT MET HOLMES BUILDING WILL INSTALL A FALL PROTECTION DEVISE. IF ANY
		O 36"x36"	36 1/4"x36 1/4"	OF THE 1st FLOOR WINDOWS ARE GREATER THAN 72" ABOVE GRADE, THE FALL PROTECTION
		P 32"x54" DORMER	32 1/4"x54 1/4"	DEVISE WILL BE INSTALLED ON-SITE BY OTHERS. SUBJECT TO LOCAL APPROVAL.
		Q 24"x60"	24 1/4"x60 1/4"	

NOTE:
 ANY REQUIREMENTS FOR WHOLE HOUSE VENTILATION SYSTEMS ARE TO BE MET AND PROVIDED ON SITE BY OTHERS PER LOCAL CODE AND ARE NOT THE RESPONSIBILITY OF HOLMES BUILDING SYSTEMS.

NOTE:
 ALL 1st AND 2nd FLOOR WINDOWS SHALL BE INSTALLED WITH THE LOWEST PART OF THE CLEAR OPENING LOCATED GREATER THAN 24" ABOVE THE FLOOR. IF THIS REQUIREMENT IS NOT MET HOLMES BUILDING WILL INSTALL A FALL PROTECTION DEVISE. IF ANY OF THE 1st FLOOR WINDOWS ARE GREATER THAN 72" ABOVE GRADE, THE FALL PROTECTION DEVISE WILL BE INSTALLED ON-SITE BY OTHERS. SUBJECT TO LOCAL APPROVAL.